

Roll Interior 50

Product Type

Roll Plaster Interior is strong, fine texture coating for interior and exterior use. It improves appearance and renders it more distinct. It is applicable in a quick safe and short time.

Areas Of Use

Plaster Interior Roll is recommended for exterior and interior use, such as masonry surfaces, concrete, wood block, walls cement, asbestos.

Specific Characteristic:

For an even texture appearance, different attractive finishing can be applied on Plaster Interior roll such as grooving or stippling. The decoration can be implemented accordingly to any particular architectural style.

Composition

Plaster Interior Roll base is styrene Acrylic Latex emulsion blended with prime chloride type, titanium dioxide pigment, and suitable additives to provide quick and safe application.

Technical Data

Colors: White ready - mix color
(refer to catalogue)

Finish: Matt

Drying Time: 1/2 - 1 hour

To touch: 2 hours

Curing: Physical Evaporation

Full Hardness: one week

Thinning: 25% water 1 st coat and 1 l. 2nd coat

Clean up solvent: Water and Soap

Practical Coverage: 22-25m² / 1US Barril

Depending on surface porosity,
method of application and texture requirement

Packaging: Available in 1US Barril

Usage Instruction

Pretreatment:

New Surfaces

Before usage, clear all surfaces from grease, oil, dirt and foreign matters which could prevent proper adhesion.

Application

Dilute for the 25% for the 1st coat by water. Allow overnight drying. If necessary, apply final coat which is diluted in water only.

Use large medium or fine pore foam roller for application.

Precaution:

- 1- Do not apply paint if air or surfaces temperature is below 10°C.
- 2- Employ several applicators for large walls, and stop the work only when the application is completed to avoid mistakes.