

Roll Acrylic 40

Interior - Exterior

Product Type

Plaster Roll Acrylic is high build coarse, texture coatings for interior and exterior use. It improves appearance and renders it more distinct.

Areas Of Use

Plaste Roll Acrylic is recommended for exterior and interior use, such as masonry surfaces, concrete, wood block, walls cement, asbestos.

Specific Characteristic

It possesses an outstanding adherence for all surfaces due to its weather resistance, flexibility and durability. For an even texture appearance different attractive finishing can be applied on Plastic Acrylic roll such as grooving or stippling. The decoration can be implemented accordingly to any particular architectural style.

Composition

Plaste Roll Acrylic base is acrylic latex blended with prime chloride type, titanium dioxide pigment and suitable additives to provide rapid and safe application.

Technical Data

Colors: White ready - mix color (refer to catalogue)

Finish: Matt

Drying Time: at 25°C / 50% R H, 1/2 hour

Weight: 1.40 Gr./ cm³

To touch: 2 hours

Full Hardness: 1 week

Thinning: 25% water 1st coat and 1l. 2nd coat

Clean up solvent: Water and Soap

Practical Coverage: 17-20 m² / 1 US Barril

Depending on surface porosity, method of application and texture requirement

Packaging: Available in 1 US Barril Pails

Usage Instruction

Pretreatment:

New Surfaces

Before usage, clear all surfaces from grease, oil, dirt and foreign matters which could prevent proper adhesion.

Application

Dilute for the 25% for the 1st coat by water. Allow overnight drying. If necessary, apply final coat which is diluted in water only.

Use large medium or fine pore foam roller for application.

Precaution:

1- Do not apply paint if air surfaces temperature is below 10°C.

2- Hire several applicators for large walls, and stop the work only when the application is completed to avoid mistakes.

3- Avoid application when walls are exposed to sunbeams in summer.