

## Sealowhite 1200

Interior - Exterior

### Product Type

Sealowhite 1200 is an exceptional waterborne latex for sealing walls and ceilings.

### Specific Characteristic

It is specially formulated to seal-off new walls and ceilings as well as any type of old painted surfaces, so it will give a sound surface for further painting.

### Areas of Use

Sealowhite 1200 can be used on stucco , cement, compound, chipboard, gypsum board, fiber glass texture as well as new and previously painted surfaces.

### Technical Data

**Colors:** White

**Viscosity:** 120 KUs @ 25°C

**Weight:** 8.8 lbs or 4 kgs/U.S.

**Coverage:** 50 - 60m<sup>2</sup> / Gal

**Drying Time:** 30 min can be repainted after 4 hours

**Curing:** Physical evaporation

**Solvent:** Water

**Solids:** 35% weight / 20%Volume

## Usage Instruction

### Pretreatment:

#### New Surfaces

Before usage, clean all surfaces from grease, oil, dirt and foreign matters which could prevent proper adhesion.

#### Repainting

Rinse carefully with water to remove loose paint or excessive chalking, before the usage of the new paint.

#### Thinning:

Dilute 40% of the paint for the 1st coat, and 30% of the paint of the 2nd and 3rd coat.

Thinning: Plaster Sealowhite 1200 is packaged in 1US Gallon and 1US barril.

#### Application:

Apply the paint with a roller or a brush. It can also be sprayed with airless spray gun.

#### Cleaning:

Clean tools immediately with water after use