

Bouchard

Product Type

Plaster Bouchard is a high quality, heavy duty, for exterior and interior coating. It is used for protection and esthetic reasons on masonry surfaces, which gives the walls a cutting stone look.

Areas Of Use

Plaster Bouchard is used for interior and exterior surfaces, masonry surfaces and concrete walls.

Technical Data

Specific Gravity: 1.25 +/- 0.05
% solid, by weight: 82.50
Finish: bouchard - looking effect
Dry Film thickness/coat: 1.2 to 2 mm
dry to touch: 3 hours @ 21°C
Dilution: Water
Spreading Rate: 12 - 14 m²/Drum
Application Mode: Stainless Steel trowel
Finishes: Bouchard - looking effect

Specific Characteristic:

Plaster Bouchard is based on special elastic polymers in aqueous dispersion. It has a high quality inorganic pigments, extenders and additives. Combining Bouchard with some selected Italian aggregate, and about one 1mm granulometry gives a fine roughest effect finishing. All these elements give the product its workability and durability.

Usage Instruction

Pretreatment:

New Surfaces

Before usage, clear the block or concrete surface from grease, oil, dirt and foreign matters

Application

-After Cleaning the surface, cover all cracks with Deter 525, apply primer coat "bouchard primer serie 40" diluted 30-40% water (60-70 m²/drum)
- Dilute with 25-30% water if a second primer is needed.
- For the finishing, apply Bouchard by stainless steel trowel (5% dilution with water)
Second coat by plastic steel trowel.