

Deter Water Proofs 520 clear

Product Type

Deter Water Proofs compound, is a viscous plastic liquid especially designed for roof protection. It has a strong adhesion, seals up absorbent surfaces, fills hair-line cracks, stops leakage and forms an impermeable film surface.

Areas of Use

Deter Water Proofs is specially formulated for roof.

Features and Benefits

Deter Water Proof is weather and U.V resistant, no discoloration, helps filling the cracks. Usually the durability of the coating is at least five years, taking into consideration the film thickness, climatic condition and proper application. As well, Deter water proofing is a rubber structure compound. When dry, it forms a seamless thick possessing maximum flexibility and elongation properties (400%).

Usage Instruction

Pretreatment:

Surfaces

All surface must be cleaned and cleared from any particles, dirt, dust or oil, Porous or badly weathered surfaces must be cleaned and primed.

Application

Apply by long haired soft brushes or rollers.

Apply first coat with primer deter 500 diluted with water (10-15%)

Allow to dry at least 24 hours.

Apply the second coat in a cross direction to the first coat with deter W.P diluted (10-15%) with water.

When a third coat is necessary, apply an interval of 24 hours.

Precautions

Avoid application at temperature below 10°C or when rain or fog can be expected during the first stage of the drying period.

Packaging

1 Drum

1 US Gallon

1 kilo

Spreading Rate

Depending upon the surface of the substrate, 1 kilo of deter should cover 1-2 sq. meter to be applied in two to three coats in a cross direction.