

## **Deter Water Proofs 525 Pigmented**

### **Product Type**

Deter Water Proofs compound, is a viscous plastic liquid especially designed for roof protection. It has a strong adhesion, seals up absorbent surfaces, fills hair-line cracks, stops leakage and forms an impermeable film surface.

### **Areas of Use**

Deter Water Proofs is specially formulated for roof.

### **Features and Benefits**

Deter Water Proofs is weather and U.V resistant, no discoloration, helps filling the cracks. Usually the durability of the coating is at least five years, taking into consideration the film thickness, climatic condition and proper application. As well, Deter water proofing is a rubber structure compound. When dry, it forms a seamless thick film possessing maximum flexibility and elongation properties (400%).

## **Usage Instruction**

### **Pretreatment:**

#### **Surfaces**

All surface must be cleaned and cleared from any particles, dirt, dust or oil, Porous or badly weathered surfaces must be cleaned and primed.

#### **Application**

Apply by long haired soft brushes or rollers. Apply first coat with primer deter 500 diluted with water (10-15%) Allow to dry at least 24 hours. Apply the second coat in a cross direction to the first coat with deter W.P diluted 10-15% with water. When a third coat is necessary, apply at an interval of 24 hours.

#### **Precautions**

Avoid application at air and floor temperatures below 10°C or when rain or fag can be expected during the first stage of the drying period.

#### **Packaging**

1 Drum  
1 US Gallon  
1 kilo

#### **Spreading Rate**

Depending upon the surface of the substrate, 1 kilo of deter should cover 1-2 sq. meter to be applied in two to three in a cross direction.