



For Trading & Contracting C.R 4069 BAABDA

Gloss Emulsion 800

Anti Carbonation - Interior - Exterior

Product Type

Plaster Gloss Emulsion 800 is awaterborne gloss, it is a top quality resin base paint which can be used on new or repainting walls and ceilings whether it is indoor or outdoor. It is applicable only on washable and drable facades.

Areas of Use

Plaster Gloss Emulsion 800 is ideal for living rooms, bedrooms, offices, kitchens, bathrooms. it can be used on plaster, concrete and gypsum board, texture, wallpaper, vinyl and previously painted surfaces.

Specific Charasteristic

Plaster Gloss Emulsion 800 has a very good adhesion to latex, alkyd and oil painted surfaces.
Recommented for masking and hiding. it dries quickly and sustain the same color with time.

Technical Data

Binder: Emulsion, Resin Based

Viscosity: 90KU's @ 25°C Weight: 4kg / US.Gal

Coverage: 40 m² / Gal

Drying Time: 30 min can be repainted after 4 hours

Curing: Physical evaporation

Solvent: Water

Flash Point: non-flammable

Usage Instruction

Pretreatment:

New Surfaces

Clean the surface from dust, dirt and loose particles. Apply Sealer or undercoat. Apply two final coats of Emulsion Gloss 800

Repainting

Rinse thoroughly with water, apply primer sealer or undercoat. Apply two coats of Emulsion Gloss 800

Thinning:

Dilute 40% of the paint for the 1st coat, and 30% of the paint of the 2nd and 3rd coat.

Application:

Apply the paint with a roller or a brush. It can also be sprayed with airless spray gun.

Cleaning:

Clean tools immediately with water after use