

Emulsion Acrylic 600

Interior - Exterior

Product Type

Plaster Emulsion Acrylic 600 is an outstanding water-based paint which can be used on new and old painted walls whether they are interior or exterior.

Areas of Use

Plaster Emulsion Acrylic 600 can be used on all sorts of facades such as, concrete, cement, textured coating, as well as previously painted surfaces.

Specific Characteristic

Emulsion Plaster Acrylic 600 paint is ideal for interior and exterior use. It is designed to withstand all weather changes without blistering, peeling, cracking or chalking. These high performance coatings are easy to apply, very efficient and durable.

Technical Data

Colors: White and selected standard colors

Viscosity: 11 poise @ 25°C

Weight: 1.35 Gr./ cm³

Coverage: 45 - 50m² / Gal

Drying Time: 30 min can be recoated after 4 hours

Curing: Physical evaporation

Solvent: Water

Solids: Brush, roll, airless.

Usage Instruction

Pretreatment:

New Surfaces

Clean the surface from dust, dirt and loose particles. Apply Sealer or undercoat. Apply two final coats of Emulsion Latex 600

Repainting

Rinse thoroughly with water, apply primer sealer or undercoat. Apply two coats of Emulsion Acrylic 600

Thinning:

Dilute 40% of the paint for the 1st coat, and 30% of the paint of the 2nd and 3rd coat.

Application:

Apply the paint with a roller or a brush. It can also be sprayed with airless spray gun.

Cleaning:

Clean tools immediately with water after use