

Emulsion Acrylic 200

Interior - Exterior

Product Type

Plaster Emulsion latex 200 is a water borne latex emulsion paint which can be used on washable and durable surfaces such as new walls or indoor and outdoor ceilings.

Areas of Use

Plaster 200 can be used on: Plaster, Concrete and speckled surface, wood fibership and gypsum board, texture, wallpaper and previously painted surfaces.

Specific Charasteristic

Latex 200 has an excellent adhesion among other latex painted surfaces. It can be used for maintenance, masking and repairing painting. It dries quickly and sustain the same color with time.

Technical Data

Colors: White & Selected standard colors

Viscosity: 20 poise @ 25°C

Weight: 1.35 gr./cm³

Coverage: 50 - 45m² / Gal

Drying Time: 30 min can be recoated after 4 hours

Curing: Physical evaporation

Solvent: Water

Application: Brush - roll - airless

Usage Instruction

Pretreatment:

New Surfaces

Clean the surface from dust, dirt and loose particles. Apply Sealer or undercoat. Apply 2 final coats of Emulsion Latex 200

Repainting

Rinse thoroughly with water, apply primer sealer or undercoat. Apply 2 coats of Emulsion Latex 200

Thinning:

Dilute 40% of the paint for the 1st coat, and 30% of the paint of the 2nd and 3rd coat.

Cleaning:

Clean tools immediately with water after use

Application:

Apply the paint with a roller or a brush. It can also be sprayed with airless spray gun.