

## **Emulsion Vinyl 100**

*Interior - Exterior*

### **Product Type**

Plaster Emulsion Vinyl 100 is a waterborne latex emulsion paint which can be used on efficient and durable surface. It can be used indoor and outdoor, for new or repainting walls and ceilings.

### **Areas of Use**

Plaster Emulsion Vinyl 100 can be used on plaster ,concrete, sand speckled surfaces, wood fibership board, gupsum board, texture, wallpaper and previously painted surfaces.

### **Technical Data**

**Colors:** White & Selected standard colors

**Viscosity:** 24 poise @ 25°C

**Weight:** 1.41 Gr./cm<sup>3</sup>

**Coverage:** 45 - 40m<sup>2</sup> / Gal

**Drying Time:** 30 min can be recoated after 4 hours

**Curing:** Physical evaporation

**Solvent:** Water

**Application:** Brush - roll - airless

---

## **Usage Instruction**

### **Pretreatment:**

#### **New Surfaces**

Clean the surface from dust, dirt and loose particles. Apply Sealer or undercoat. Apply two final coats of Emulsion Vinyl 100

#### **Repainting**

Rinse thoroughly with water, apply primer sealer or undercoat. Apply two coats of Emulsion Vynil 100

#### **Thinning:**

Dilute 40% of the paint for the 1st coat, and 30%of the paint of the 2nd and 3rd coat.

#### **Application:**

Apply the paint with a roller or a brush. It can also be sprayed with airless spray gun.

#### **Cleaning:**

Clean tools immediately with water after use