

Graphic Paint 60

Product Type

Plaster Graphics is a granulated acrylic based for the protection and decoration of masonry surfaces.

Areas Of Use

Graphic Paint may be used on surfaces like cement, concrete, plaster where maximum outdoor resistant is required.

Specific Characteristic:

Plaster graphics is well known for its decoration and waterproof features. It is a weather resistant paint, suitable for balconies and facades.

Composition

Plaster Graphics base is styrene acrylic latex emulsion blended with prime chloride type, titanium dioxide pigment, and suitable additives to provide quick and safe application.

Technical Data

Colors: White ready - mix color
(refer to catalogue)

Finish: Matt

Drying Time: 1 - 1/2 hour

To touch: 2 hours

Curing: Physical Evaporation

Full Hardness: one week

Thinning: 25% water 1st coat and 1l. 2nd coat

Clean up solvent: Water and Soap

Practical Coverage: 9-10m² / Baril

Packaging: Available in 1US Barril Pails

Usage Instruction

Pretreatment:

New Surfaces

Before usage, clear all surfaces from grease, oil, dirt and foreign matters which could prevent proper adhesion.

Application

Dilute 25% for the 1st coat by water. Allow overnight drying. If necessary, apply final coat which is diluted in water only. Use large medium or fine pore foam roller for application.

Precaution:

- 1- Do not apply paint if air or surfaces temperature is below 10°C.
- 2- Employ several applicators for large walls, and stop the work only when the application is completed to avoid mistakes.