

Emulsion Vinyl 300

Interior

Product Type

Plaster Emulsion Vinyl 300 is an economical quality latex flat paint, for interior walls and ceilings.

Specific Characteristic

Plaster Vinyl 300 is excellent for hiding and it is a stain resistant

Areas of Use

Plaster Emulsion Vinyl 300 can be used on new or old masonry surfaces as well as primed or previously painted woodworks and walls.

Technical Data

Colors: White & ready mix colors, as well as customer's colors

Finish: Flat

Density: 1.36 Gr./cm³

Coverage: 40 - 50m² / Gal, depending on surface porosity

Drying Time: 1 hour

To Recoat: 2 hours

Clean Up Solvent: Water

Usage Instruction

Pretreatment:

New Surfaces

Clean the surface from dust, dirt and loose particles. Apply Sealer or undercoat. Apply 2 final coats of Emulsion Latex 300

Thinning:

Dilute 40% of the paint for the 1st coat, and 30% of the paint of the 2nd and 3rd coat.

Application:

Apply the paint with a roller or a brush. It can also be sprayed with airless spray gun.

Repainting

Rinse thoroughly with water, apply primer sealer or undercoat. Apply 2 coats of Emulsion vinyl 300

Cleaning:

Clean tools immediately with water after use