

## **Plastocrete 3525**

### **Product Type**

Plaster plastocrete is a solvent based, styrene / acrylate but diene copolymers. It is a water proof paint. Plastocrete is a top quality coat, used on interior and exterior surfaces. it creates a waterproofing film once it enter is reaction with moisture, and the ultra violet resistance of the polymer, acts as a filter , preventing the film from breaking down under exposure.

### **Areas of Use**

It is used in swimming pools, masonry surfaces, tunnels, concrete walls, water reservoir and basements.

### **Features and Benefits**

This product is a long term protection against moisture and humidity, it is moisture permeable, resistant to salt, water and weather resistant, and it dries fast.

### **Technical Data**

**Specific Gravity:** 1.4±0.05

**% Solid by volume:** 51.50

**Average by film thickness/coat:** 120 microns

**Dry to touch:** 3 - 4 hours @ 21°C

**Application Method:** Roller/ Airless Spray

**Finishes:** white

**Thinner:** White Spirit

**Spreading Rates:** 3-5m<sup>2</sup> / liter

---

## **Usage Instruction**

### **Pretreatment:**

#### **Surfaces**

New concrete must be a minimum of 28 days old and possesses an open surface texture that is clear and neat.

Prepare the surface mechanically using a wire brush, or sand stone, or sand blast.

#### **Application**

After the surface has been prepared, prime all crack and wholes with plastoseal bounding and penetrating agent.

Patching with stopper

Plastocrete

Apply first coat diluted 30 - 40% mineral spirit.

**Plasmodium 3525**