

## **Primer Sealer 1050**

### *Interior*

#### **Product Type**

Plaster Acrylic Sealer 1050 is a single component water based, alkali resistant, primer sealer, designed specifically for use on masonry surfaces of all types.

#### **Specific Characteristic**

Primer Sealer 1050 protects masonry surfaces from moisture penetration by forming a clear layer. It is used under all types of alkyd, oil based and latex paints.

#### **Areas of Use**

Primer Sealer 1050 may be used on interior masonry surfaces. Filling cracks in plaster, cement, concrete, stucco and putty.

#### **Technical Data**

**Colors:** Clear

**Finish:** Glossy

**Density:** 0.95 gm/cm<sup>3</sup>

**Drying Time:** 30 mins

**Curing:** Physical evaporation

**Clean Up Solvent:** Soap and water

**Solvent:** Water

**Practical Coverage:** 50 - 60m<sup>2</sup> / gallon depending on surfaces texture and porosity.

---

## **Usage Instruction**

### **Pretreatment:**

#### **New Surfaces**

Before usage, clear all surfaces from grease, oil, dirt and foreign matters which could prevent proper adhesion.

#### **Repainting**

Rinse carefully with water to remove loose paint or excessive chalking, before the usage primer sealer 1100

#### **Thinning:**

Dilute 40% of the paint for the 1st coat, and 30% of the paint of the 2nd and 3rd coat.

**Thinning:** Plaster Sealowhite 1200 is packaged in 1US Gallon and 5US Gallons Pail.

#### **Application:**

Apply the paint with a roller or a brush. It can also be sprayed with airless spray gun.

#### **Cleaning:**

Clean tools immediately with water after use