

Primer Sealer 1100

Interior

Product Type

Plaster Acrylic Sealer 1100 is a single element water-based, alkali resistant, primer sealer, designed to be used on all type of masonry surfaces.

Areas of Use

Primer Sealer 1100 may be used on interior masonry surfaces. Filling cracks in plaster, cement, concrete, stucco and putty.

Specific Characteristic

Primer Sealer protects masonry surfaces from moisture penetration by forming a clear layer. It is used under all types of alkyd, oil based and latex paints.

Technical Data

Colors: Clear

Finish: Glossy

Density: 0.95 gm/cm³

Drying Time: 30 mins

Curing: Physical evaporation

Clean Up Solvent: Soap and water

Solvent: Water

Practical Coverage: 60-50 m²/gallon depending on surfaces texture and porosity.

Usage Instruction

Pretreatment:

New Surfaces

Before usage, clear all surfaces from grease, oil, dirt and foreign matters which could prevent proper adhesion.

Repainting

Rinse carefully with water to remove loose paint or excessive chalking, before the usage primer sealer 1100

Thinning:

Dilute 40% of the paint for the 1st coat, and 30% of the paint of the 2nd and 3rd coat.

Thinning: Plaster Sealowhite 1200 is packaged in 1US Gallon and 1US Barril

Application:

Apply the paint with a roller or a brush. It can also be sprayed with airless spray gun.

Cleaning:

Clean tools immediately with water after use