

## **Primer Deter 500**

### **Product Type**

Plaster Primer Deter is a non-pigmented product. It is chemical and scratch resistant, fresh and sea water proof. If applied on concrete or masonry surfaces, it offers an acid resistance.

### Specific Charecteristic:

Deter Sealer is a great primer for surfaces that would be covered with deter roll, thus it would ensure a long life protection against U.V. light, abrasion and water resistance.

#### Areas of Use

Deter Sealer can be used on primer sealer or finish to potable water concrete reservoirs due to its non-toxic feature. Moreover it can be used on concrete roofs, floors, walls and facades.

### Technical Data

Colors: Clear

Solvent: White Spirit

Viscosity: 80 - 85 Kus @ 25°C

Density: 1 gr/ cm<sup>3</sup>

Coverage: 20 up to 25 m<sup>2</sup>/gal

Flash Point: over 36°C To touch: about 1 hour

Hard dry to handle: about 24 hours

# **Usage Instruction**

## Pretreatment:

#### **New Surfaces**

The surface must be dry, cleaned and cleared from any particles, dirt, rust, oil or other foreign matters. Firt coat: To ensure maximum bonding surface and penetration, thin with Deter solvent at a radio of 1 to 1
Second coat: Thin up to 25% with Deter thinner allowing an interval time of at least 4 hours between

consecutive applications.

## **Packaging**

1 Drum

1 US Gallon

1 kilo

1/2 kilo

## Thinning

White Spirit

## **Application**

Brush, Roll or Spray gun.

## Cleaning

Tools must be cleaned immediately in white spirit.