

Super Enamel 900

Gloss - Semi Gloss - Matt

Product Type

Plaster Super Enamel 900, is a premium alkyd enamel, available in a high gloss, semi-gloss and matt finishing for interior and exterior usage on primed wood and metal surfaces.

Specific Charecteristic:

It possesses excellent characteristics, such as great leveling, high and constant gloss, an outstanding adherence for all surfaces due to its weather resistance, flexibility, durability and scratch proof surface. It is easy to use for masking.

Areas of Use

Plaster Super Enamel 900 can be used on primed surfaces of walls, ceilings and woodwork cabinets.

Technical Data

Colors: Standard Colors

Binder: Alkyd resin

Solvent: White Spirit

Viscosity: 85 k us @ 25C

Density: 1.2 gr/cm³ in case of Gloss
1.3 gr/cm³ in case of Matt

Solids: 50%by volume

Coverage:40 up to 50 m² /gal.

Depending on methods of application and surface porosity

Thinning: Mineral Spirit

Drying Time: 5 hours

(@25°C, and %50 Relative Humidity)

Flash Point: 36°C

Usage Instruction

Pretreatment:

New Surfaces

Clean the surface from dust, dirt and loose particles, oil, rust and foreign matter.

Iron: prime with plaster primer Red Oxide 90 or 95. Prime with plaster Undercoat 700.

Wood, Board and chip board:

Dilute the paint with white spirit.

Painted Surfaces:

Scrape - off loose paint, Sand down, remove all dust, dirt and spot prime with Plaster primers.

Finishing Coat:

Finish with one or two coats Plaster Enamel 900 series.

Packaging

1 US Gallon

1 kilo

2/1 kilo

Application

Brush, Roll or Spray gun. If rolling, post smoothing with a brush should be done.

Cleaning

Clean tools with white spirit.