

Undercoat 1700

Economical Undercoat

Product Type

Undercoat 1700 is a high end alkyd undercoat used for interiors, to use under alkyd enamels or latex paints on interior wood, trim or primed metal.

Specific Charecteristic:

Undercoat 1700 is easy to apply it possesses excellent characteristics, such as excellent sealing and enamel holdout properties, it is great for masking, good leveling, it requires only light sanding to a smooth surface to receive subsequent coats of finish enamel.

Areas of Use

Plaster Undercoat 1700 may be used on surfaces such as wood, plaster, wall board metal, masonry, and other surfaces which would generally call for an enamel finish.

Technical Data

Colors: White, ready mix colors

Finish: Matt

Solvent: Mineral Spirit

Density: 1.43 gr/cm³

Coverage: 40 up to 50 m²/gal.

Depending on methods of application and surface porosity.

Drying Time: 4 hours

To sand and recoat: overnight

Usage Instruction

Pretreatment:

New Surfaces

Clean the surface from dust, dirt and loose particles, oil, rust and foreign matter before painting the surfaces. Prime with Plaster Undercoat series 1700 diluted with %20 white spirit.

Finishing Caoat

Finish with one or two coats Plaster Super Enamel 900 series.

Packaging

1 Drum
1 US Gallon
1 kilo

Application

Brush, Roll or Spray gun. If rolling, post smoothing with a brush should be done.

Cleaning

Clean tools with white spirit.