

Undercoat 5700

Water Based System

Product Type

Undercoat 5700 is a high end water based undercoat, to use under Latex Paints on interior walls and soffits.

Specific Charecteristic:

Undercoat 5700 is easy to apply, it possesses excellent characteristics, such as excellent sealing and enamel holdout properties, it is great for masking, good leveling, it requires only light sanding to a smooth surface to receive subsequent coats of finish enamel.

Areas of Use

Plaster Undercoat 5700 may be used on surfaces such as wood, plaster, wall board metal, masonry, and other surfaces which would generally call for an enamel finish.

Technical Data

Colors: White, ready mix colors
Finish: Matt
Clean Up: Water
Density: 1.43 gr/cm³
Coverage: 150 m²/Drum (1 coat)
Drying Time: 2 hours
To sand and recoat: overnight

Usage Instruction

Pretreatment:

New Surfaces

Clean the surface from dust, dirt and loose particles, oil, rust and foreign matter before painting the surfaces. Prime with Plaster Undercoat series 5700 diluted with 20% white spirit.

Finishing Caoat

Finish with one or two coats Plaster latex.

Packaging

1 Drum
1 US Gallon
1 kilo

Thinning

Use water

Application

Brush, Roll or Spray gun.

Cleaning

Clean tools with white spirit.