

Varnish 1600

Gloss - Semi Gloss - Matt

Product Type

Plaster Varnish 1600 clear, Alkyd Varnish, resistant to weather and industrial fumes with an excellent proof to fresh and salt water.

Specific Charecteristic:

It possesses excellent characteristics, such as great leveling, high and consistant gloss, an outstanding adherence for all surfaces due to its weather resistance, flexibility, durability and scratch proof surface. It is easy to use for masking.

Areas of Use

Plaster Varnish is used for interior and exterior surfaces, it has a good flexibility and is best suited for wooden substrates.

Technical Data

Colors: Clear Straw

Binder: Alkyd resin

Finish: Gloss, Semi Gloss, Matt

Coverage: 45 up to 50 m² /gal.

Depending on method of application and surface porosity

Thinning: Mineral Spirit

Drying Time: 5 hours

(@25°C, and 50%Relative Humidity)

Flash Point: 36°C

Usage Instruction

Pretreatment:

New Surfaces

Clean the surface from dust, dirt and loose particles, oil, rust and foreign matter.

Iron: prime with plaster primer Red Oxide 90 or 95.

Wood, Board and chip board:

Prime with Plaster Varnish diluted with white spirit.

Painted Surfaces:

scrape - off loose paint, Sand down, remove all dust, dirt and spot prime with Plaster Primers.

Packaging

1 US Gallon

1 kilo

2/1 kilo

Application

Apply thin uniform coats with a clean brush . three coats would be needed for optimum results.

Cleaning

Clean tools with white spirit.