

Water repellent 550

Product Type

Plaster Repellent is a « Ready to use» product, it reduces the absorption of materials such as concrete or mortar without ruining breathing capacity. It is a water proof product due to its silicone based and colorless liquid compound that penetrates the pores of the treated surface. It protects the masonry surface from moisture absorption, dirt and dust.

Areas of Use

Plaster Repellent is mainly used for façade and building elements exposed to heavy rain.

Features and Benefits

complies with the Test BS 3826

It is a non-film product creating resin without altering the aesthetic appearance. It is colorless and water resistant but lets humidity escape. Moreover Plaster Repellent minimizes the efflorescence, and reduces the deterioration by reducing the freeze, as well as masonry cleaning costs.

Usage Instruction

Pretreatment:

New Surfaces

All surface must be cleaned and cleared from any particles, dirt, dust or oil. Porous or badly weathered surfaces must be cleaned and primed.

Application

Apply by brush, spray gun or rollers. Applying two coats are usually sufficient. It is applied to the substrate to ensure complete saturation.

Precautions

Avoid application at temperature below 10°C or when rain or fog can be expected during the first stage of the drying period.

Packaging

Plaster Water Repellent supplied in:
1 Drum (18,5 lt)
1 US Gallon (3.785 lt)
1 kilo

Coverage

Depending on the porosity of the surface 20 - 25 m² / gallon